

MACHINED RING
NEEDLE ROLLER
BEARINGS


SEALED, WITH INNER RING




NA49UU,NA69UU(d≤30)




NA69UU



NA49UU,NA69UU(d ≤ 30)



NA69UU



■NA49UU,NA69UU,SEALED TYPE

Prepacked Grease

Shaft Diameter (mm)	Designation		Dimensions (mm)							Standard mounting dimensions (mm)		Basic dynamic load rating	Basic static load rating	Limiting speed (GREASE)	Mass	Usable bearing designation	
	NA 49UU	NA 69UU	d	D	C	B	r's min	F	da		Da	Cr	Cor	rpm	g (approx)	OUTER RING	INNER RING
									MIN	MAX	MAX	N	N				
10	NA 4900UU	—	10 ⁰ _{-0.008}	22	13	14	0.3	14	12	13	20	8 000	8 500	14 000	25	RNA4900UU	IRZ101414
12	NA 4901UU —	— NA 6901UU	12 ⁰ _{-0.008} 12	24 24	13 22	14 23	0.3 0.3	16 16	14 14	15 15	22 22	8 400 15 600	9 300 20 400	12 000 12 000	28 46	RNA4901UU RNA6901UU	IRZ121614 IRZ121623
15	NA 4902UU —	— NA 6902UU	15 ⁰ _{-0.008} 15	28 28	13 23	14 24	0.3 0.3	20 20	17 17	19 19	26 26	9 600 18 400	11 700 27 100	9 500 9 500	36 63	RNA4902UU RNA6902UU	IRZ152014 IRZ152024
17	NA 4903UU —	— NA 6903UU	17 ⁰ _{-0.008} 17	30 30	13 23	14 24	0.3 0.3	22 22	19 19	21 21	28 28	10 300 19 800	13 100 30 600	8 500 8 500	40 69	RNA4903UU RNA6903UU	IRZ172214 IRZ172224
20	NA 4904UU —	— NA 6904UU	20 ⁰ _{-0.010} 20	37 37	17 30	18 31	0.3 0.3	25 25	22 22	24 24	35 35	17 900 33 000	20 500 44 500	7 500 7 500	78 140	RNA4904UU RNA6904UU	IRZ202518 IRZ202531
25	NA 4905UU —	— NA 6905UU	25 ⁰ _{-0.010} 25	42 42	17 30	18 31	0.3 0.3	30 30	27 27	29 29	40 40	20 300 39 200	25 100 58 600	6 500 6 500	93 162	RNA4905UU RNA6905UU	IRZ253018 IRZ253031
30	NA 4906UU —	— NA 6906UU	30 ⁰ _{-0.010} 30	47 47	17 30	18 31	0.3 0.3	35 35	32 32	34 34	45 45	21 600 40 100	28 400 63 100	5 500 5 500	106 185	RNA4906UU RNA6906UU	IRZ303518 IRZ303531
35	NA 4907UU —	— NA 6907UU	35 ⁰ _{-0.012} 35	55 55	20 36	21 37	0.6 0.6	42 42	39 39	41 41	51 51	30 100 51 600	46 300 92 600	4 500 4 500	179 320	RNA4907UU RNA6907UU	IRZ354221 IRZ354237
40	NA 4908UU —	— NA 6908UU	40 ⁰ _{-0.012} 40	62 62	22 40	23 41	0.6 0.6	48 48	44 44	47 47	58 58	37 200 63 700	58 300 116 700	4 000 4 000	245 440	RNA4908UU RNA6908UU	IRZ404823 IRZ404841
45	NA 4909UU —	— NA 6909UU	45 ⁰ _{-0.012} 45	68 68	22 40	23 41	0.6 0.6	52 52	49 49	51 51	64 64	38 800 66 700	63 400 126 500	3 500 3 500	290 510	RNA4909UU RNA6909UU	IRZ455223 IRZ455241
50	NA 4910UU —	— NA 6910UU	50 ⁰ _{-0.012} 50	72 72	22 40	23 41	0.6 0.6	58 58	54 54	57 57	68 68	41 300 70 800	71 100 142 200	3 500 3 500	300 530	RNA4910UU RNA6910UU	IRZ505823 IRZ505841