



SEPARABLE
NEEDLE ROLLER
BEARINGS
WITH INNER RING




NAF




NAFW



NAF



NAFW



NAF(W) TYPE

Shaft Diameter (mm)	Designation	Dimensions (mm)								Standard mounting dimensions (mm)		Basic dynamic load rating	Basic static load rating	Limiting speed *	Mass	Usable bearing designation		
											Db							
									MIN	MAX								
	NAF(W)	d	D	C	r's min	F	db	Da MAX				Cr N	Cor N	rpm	g (approx)	OUTER RING	INNER RING	
6	NAF 61710	6 ⁰ _{-0.008}	17	10	0.3	10	12.4	15		8	9.7	10.4	4 100	4 500	28 000	14	RNAF101710	IR61010
7	NAF 72012	7 ⁰ _{-0.008}	20	12	0.3	10	13.5	18		9	9.7	10.4	6 000	6 000	28 000	23	RNAF102012	IR71012
9	NAF 92212	9 ⁰ _{-0.008}	22	12	0.3	12	17.5	20		11	11.5	12.4	9 000	8 400	26 000	24	RNAF122212	IR91212
10	NAF 102213	10 ⁰ _{-0.008}	22	13	0.3	14	17.6	20		12	13	14.6	7 800	9 400	24 000	26	RNAF142213	IR101413
	NAFW 102220	10 ⁰ _{-0.008}	22	20	0.3	14	17.6	20		12	13	14.6	10 800	14 200	24 000	40	RNAFW142220	IR101420
	NAF 102612	10 ⁰ _{-0.008}	26	12	0.3	14	19.4	24		12	13	14.6	9 800	9 700	24 000	36	RNAF142612	IR101412
12	NAF 122413	12 ⁰ _{-0.008}	24	13	0.3	16	19.6	22		14	15	16.6	8 600	11 000	23 000	30	RNAF162413	IR121613
	NAFW 122420	12 ⁰ _{-0.008}	24	20	0.3	16	19.6	22		14	15	16.6	11 900	16 700	23 000	45	RNAFW162420	IR121620
	NAF 122812	12 ⁰ _{-0.008}	28	12	0.3	16	21.4	26		14	15	16.6	10 500	10 900	23 000	40	RNAF162812	IR121612
15	NAF 152813	15 ⁰ _{-0.008}	28	13	0.3	20	23.6	26		17	19	20.6	9 600	13 500	20 000	37	RNAF202813	IR152013
	NAFW 152826	15 ⁰ _{-0.008}	28	26	0.3	20	23.6	26		17	19	20.6	16 500	27 100	20 000	76	RNAFW202826	IR152026
	NAF 153212	15 ⁰ _{-0.008}	32	12	0.3	20	25.4	30		17	19	20.6	12 400	14 300	20 000	51	RNAF203212	IR152012
17	NAF 173013	17 ⁰ _{-0.008}	30	13	0.3	22	25.6	28		19	21	22.6	10 200	15 200	18 000	43	RNAF223013	IR172213
	NAFW 173026	17 ⁰ _{-0.008}	30	26	0.3	22	25.6	28		19	21	22.6	17 600	30 300	18 000	85	RNAFW223026	IR172226
	NAF 173516	17 ⁰ _{-0.008}	35	16	0.3	22	27.8	33		19	21	22.6	17 600	20 900	18 000	77	RNAF223516	IR172216
	NAFW 173532	17 ⁰ _{-0.008}	35	32	0.3	22	27.8	33		19	21	22.6	30 200	41 900	18 000	155	RNAFW223532	IR172232
20	NAF 203517	20 ⁰ _{-0.010}	35	17	0.3	25	29.5	33		22	24	25.6	17 300	26 600	16 000	75	RNAF253517	IR202517
	NAFW 203526	20 ⁰ _{-0.010}	35	26	0.3	25	29.5	33		22	24	25.6	22 500	37 200	16 000	114	RNAFW253526	IR202526
	NAF 203716	20 ⁰ _{-0.010}	37	16	0.3	25	30.4	35		22	24	25.6	19 400	24 500	16 000	80	RNAF253716	IR202516
	NAFW 203732	20 ⁰ _{-0.010}	37	32	0.3	25	30.4	35		22	24	25.6	33 200	49 000	16 000	158	RNAFW253732	IR202532
25	NAF 254017	25 ⁰ _{-0.010}	40	17	0.3	30	34.5	38		27	29	30.6	18 600	31 100	13 000	88	RNAF304017	IR253017
	NAFW 254026	25 ⁰ _{-0.010}	40	26	0.3	30	34.5	38		27	29	30.6	24 200	43 400	13 000	136	RNAFW304026	IR253026
	NAF 254216	25 ⁰ _{-0.010}	42	16	0.3	30	35.4	40		27	29	30.6	20 800	28 300	13 000	94	RNAF304216	IR253016
	NAFW 254232	25 ⁰ _{-0.010}	42	32	0.3	30	35.4	40		27	29	30.6	35 700	56 800	13 000	187	RNAFW304232	IR253032
30	NAF 304517	30 ⁰ _{-0.010}	45	17	0.3	35	39.5	43		32	34	35.6	20 500	36 900	11 000	100	RNAF354517	IR303517
	NAFW 304526	30 ⁰ _{-0.010}	45	26	0.3	35	39.5	43		32	34	35.6	26 600	51 600	11 000	155	RNAFW354526	IR303526
	NAF 304716	30 ⁰ _{-0.010}	47	16	0.3	35	40.4	45		32	34	35.6	23 000	33 800	11 000	108	RNAF354716	IR303516
	NAFW 304732	30 ⁰ _{-0.010}	47	32	0.3	35	40.4	45		32	34	35.6	39 500	67 800	11 000	215	RNAFW354732	IR303532

* Suitable for oil lubrication. In case of grease lubrication, down to 50% of this value.


SEPARABLE
NEEDLE ROLLER
BEARINGS
WITH INNER RING




NAF




NAFW



NAF



NAFW



NAF(W) TYPE

Shaft Diameter (mm)	Designation	Dimensions (mm)					Standard mounting dimensions (mm)				Basic dynamic load rating	Basic static load rating	Limiting speed *	Mass	Usable bearing designation		
	NAF(W)	d	D	C	<i>f</i> 's min	F	db	Da MAX	da		Db	Cr N	Cor N	rpm	g (approx)	OUTER RING	INNER RING
35	NAF 355017	35	50	17	0.3	40	43.5	48	37	39	40.8	22 200	42 700	10 000	115	RNAF405017	IR354017
	NAFW 355034	35 ₀	50	34	0.3	40	43.5	48	37	39	40.8	38 000	85 300	10 000	230	RNAFW405034	IR354034
	NAF 355520	35 _{-0.012}	55	20	0.3	40	45.2	53	37	39	40.8	31 500	48 000	10 000	188	RNAF405520	IR354020
	NAFW 355540	35	55	40	0.3	40	45.2	53	37	39	40.8	53 900	96 000	10 000	375	RNAFW405540	IR354040
40	NAF 405517	40	55	17	0.3	45	48.5	53	42	44	45.8	23 200	47 200	10 000	129	RNAF455517	IR404517
	NAFW 405534	40 ₀	55	34	0.3	45	48.5	53	42	44	45.8	39 900	94 200	10 000	255	RNAFW455534	IR404534
	NAF 406220	40 _{-0.012}	62	20	0.3	45	50.9	60	42	44	45.8	33 200	53 300	9 000	236	RNAF456220	IR404520
	NAFW 406240	40	62	40	0.3	45	50.9	60	42	44	45.8	57 000	106 900	9 000	475	RNAFW456240	IR404540
45	NAF 456220	45	62	20	0.3	50	54.2	60	47	49	50.8	27 100	59 300	8 000	197	RNAF506220	IR455020
	NAFW 456240	45 ₀	62	40	0.3	50	54.2	60	49	49.5	50.8	46 400	118 700	8 000	389	RNAFW506240	IR455040
	NAF 457220	45 _{-0.012}	72	20	0.6	55	60.9	68	49	54	55.8	37 400	66 400	7 500	340	RNAF557220	IR455520
	NAFW 457240	45	72	40	0.6	55	60.9	68	49	54	55.8	64 100	132 400	7 500	685	RNAFW557240	IR455540
50	NAF 506820	50	68	20	0.6	55	59.5	64	54	54.5	55.8	28 500	66 000	7 500	230	RNAF556820	IR505520
	NAFW 506840	50 ₀	68	40	0.6	55	59.5	64	54	54.5	55.8	48 900	132 400	7 500	465	RNAFW556840	IR505540
	NAF 507820	50 _{-0.012}	78	20	1	60	66.3	73	55	59	60.8	38 900	71 700	6 500	390	RNAF607820	IR506020
	NAFW 507840	50	78	40	1	60	66.3	73	55	59	60.8	66 700	143 200	6 500	775	RNAFW607840	IR506040
55	NAF 558530	55 ₀	85	30	1	65	72	80	60	63	66	59 300	127 500	6 000	680	RNAF658530	IR556530
	NAFW 558560	55 _{-0.015}	85	60	1	65	72	80	60	63	66	102 000	254 000	6 000	1 380	RNAFW658560	IR556560
60	NAF 609030	60 ₀	90	30	1	70	77	85	65	68	71	61 200	135 300	5 500	740	RNAF709030	IR607030
	NAFW 609060	60 _{-0.015}	90	60	1	70	77	85	65	68	71	104 900	271 600	5 500	1 470	RNAFW709060	IR607060
65	NAF 659530	65 ₀	95	30	1	75	82	90	70	73	76	63 200	144 200	5 500	800	RNAF759530	IR657530
	NAFW 659560	65 _{-0.015}	95	60	1	75	82	90	70	73	76	108 900	289 300	5 500	1 570	RNAFW759560	IR657560
70	NAF 7010030	70 ₀	100	30	1	80	87	95	75	78	81	64 900	153 000	5 000	840	RNAF8010030	IR708030
	NAFW 7010060	70 _{-0.015}	100	60	1	80	87	95	75	78	81	111 800	306 000	5 000	1 670	RNAFW8010060	IR708060
75	NAF 7510530	75 ₀ -0.015	105	30	1	85	92	100	80	83	86	66 600	160 800	4 800	890	RNAF8510530	IR758530
80	NAF 8011030	80 ₀ -0.015	110	30	1	90	97	105	85	88	91	69 500	173 600	4 500	930	RNAF9011030	IR809030
85	NAF 8511530	85 ₀ -0.020	115	30	1	95	102	110	90	93	96	70 900	182 400	4 200	970	RNAF9511530	IR859530
90	NAF 9012030	90 ₀ -0.020	120	30	1	100	107	115	95	98	101	72 600	191 200	4 000	1 040	RNAF10012030	IR9010030

* Suitable for oil lubrication. In case of grease lubrication, down to 50% of this value.